

## SUPER NOVA GASOLINE

**Super Nova Gasoline** is SAE 10W-30 & 20W-50, are “fighting grade” mineral base superior quality shear stable multi-grade motor oils. Superior quality multi-grade engine oil using the latest additive technology and suitable for most modern passenger cars using gasoline engines. Designed for year-round use in gasoline engines operating in the most arduous conditions in all desert climates.

Super Nova Special can satisfy the service fill requirements of all major European, Korean, Japanese, Chinese and US car manufacturers.

### Applications

Super Nova Gasoline makes a wide range of applications possible and ensures safe operation under all climatic operating conditions. This oil meets the requirements of major US and European manufactures for long drain intervals and complies to the US and European requirements, results perform without problem in wide variations of temperature and wear protection even under most severe hot and dusty climatic conditions of all motor vehicle.

### Performance Level

API SL

ACEA A2/B2-96

### Benefits

- High Viscosity Index: An exceptionally high VI ensures easy starting in cold weather plus a resilient oil film at high temperature due to superior thermal stability.
- Extended drain intervals and reduce oil consumptions.
- Prolong Engine Life, safer year-round operation with advance additives technology keeps engine clean and up to mark results reduces wear and tear.
- Low oil consumption, even with hot climatic desert conditions.
- Avoid rust, corrosion inhibition and provides outstanding protection of engine surface and internal engine parts.
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit full product benefits of Super Nova Gasoline Oil SAE, a complete oil change is recommended.

TYPICAL CHARACTERISTICS*			SAE GRADE & VALUES
Properties	Units	ASTM Method	20W-50
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D-445	188.1
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D-445	19.8
Viscosity Index	-	ASTM D-2270	122
Specific Gravity @ 15°C	-	ASTM D-4052	0.892
Pour Point °C	°C	ASTM D-97	-27
Flash Point COC	°C	ASTM D-92	240
Code			1014

Super Nova Gasoline is premium multi-grade oil of Taqah Lubricants.

**Note:** \* The information/figures are of our current productions, it's qualifies standard specifications slight variations may occur.

For more information visit [energylubs.com](http://energylubs.com) / [taqah.sa](http://taqah.sa) or contact our Head Office KSA – Jeddah 1<sup>st</sup> Industrial City – 5<sup>th</sup> Phase. T: 920004059

